



Serie T

Technical sheet



Compact size, large capabilities

Technology and design. The T Series is designed for maximum ease of use. Frequency even 2.4 GHz. Robust and ergonomic. IP 65 Casing Protection Grade. 1000 hours' work with no recharge. REMsys code®.

Technical features

- Dual Band frequency: 433 MHz / 60 channels and 870 MHz / 12 channels
- Frequency: 418 MHz / 11 channels China
- Frequency: 915 MHz / 51 channels USA-Canada
- Commands: on/off
- Hamming code > 4
- Maximum number of simultaneous commands (according to model): 8
- Command response time: 50 ms
- Active emergency/stop response time: 50 ms
- Passive emergency response time: 1 s
- Operating and storage temperature: -20°C/+70°C
- STOP function PL D cat. 3 (EN ISO 13849-1)
- Typical range and battery life: RF power max: 70 mt, 500 hours
RF power med: 40 mt, 850 hours
RF power min: 20 mt, 1000 hours

Transmitter units

- Modulation: GFSK Manchester encoding
- Emitting power: from 1 to 10 mW
- Oscillator: PLL digital synthesizer
- Antenna: built in
- Power Supply: 3.6 Vdc
- Current demand: from 13.5 mA to 24 mA
- Built-in lithium battery: 3.6V
- Operating autonomy: over 2000 hours for 2.4 GHz models (20°C)
- Battery low warning time: 30 hrs
- Casing protection grade: IP 65
- Material: PA6 FG
- Dimensions (LxHxD): 83X174X42 mm
- Weight: 350 g

Receiver units

- Single Chip radio frequency receiver
- Antenna: Multiband internal UHF. Antenna external optional
- Command relay contact capacity: 4A (DC1/AC1) / 115V
- Stop relay contact capacity: 4A (DC1/AC1) / 115V
- RUBYBOX-T7 and RXDIN-T7
No. of on/off contacts: 15 + START + STOP + CLAX + LAMP + ABIL
- ECOBOX-T7
No. of on/off contacts: ≤ 7 + START + STOP + CLAX
- Power supply (depending on model):
DC 12-24V ±25% or AC 24-115V ±10%
Optional only RUBYBOX-T7: AC 230V ±10% 50-60 Hz
- Waterproof Casing for Outdoor use: Nylon PA6 FG, Protection Grade IP65
RUBYBOX-T7 166X279X91 mm (LxHxD)
ECOBX-T7 129X178X51 mm (LxHxD)
- MODULBOX container for installation on DIN Bar EN 50022 track - IP20
RXDIN-T7 158x75x90 mm (LxHxD)

Available receiver units:

RXDIN-T7, RUBYBOX-T7, ECOBOX-T7



Monitor tester

Self-powered display instrument to connect to the receiver, capable of acquiring the operating data of the radio control.

VIEWABLE INFORMATION:

- Working frequency and operating channel
- Signal and interference level
- Number of starts and working hours
- Number of Up and Down commands
- Relay operating diagnostics
- Active controls



Reference standards

Safety	EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013
Health	EN 62479:2010
EMC	EN 61000-6-2:2005 EN 61000-6-3:2007 + A1:2011
Radio	ETSI EN 300 220-1 V3.1.1 Final Draft ETSI EN 300 220-2 V3.1.1 Final Draft ETSI EN 301 489-1 V2.1.1 ETSI EN 301 489-3 V2.1.0 Draft

Reference rules

FCC	Rule Parts 15C
IC	RSS-247 Issue 1 RSS-GEN Issue 4
China	Radio Transmission Approval Certificate
Russia	EAC-GOST Certificate
Machinery (as applicable)	EN 60204-32:2008 EN 13557:2003 + A2:2008 UNI EN ISO 13849-1:2016

Reference directives

- Radio Equipment Directive (RED) 2014/53/EU
- Machinery Directive 2006/42/CE (as applicable)



REmdevice Srl
via Alfredo Munari, 72 - 36055 - Nove (VI) ITALY
tel +39 0424 500 262 - fax +39 0424 508 631 - info@remdevice.com
www.remdevice.com

